

FARM-MAXX

HCWR-8, HCWR-10, and HCWR-12 BATRAKES

Farm-Maxx 8, 10 and 12 Wheel High Capacity Rakes Offer You The Quality And Performance You Can Depend On!



15" tires and heavy duty 7MM teeth give you the ability to operate at high ground speeds with maximum raking efficiency and ease. A robust double acting hydraulic cylinder with heavy duty double ram design is standard for ease of operations with most tractor hydraulic systems. Each wheel features tapered roller bearings for long trouble free operation. The thick walled square tube frame is built to last for years under the most demanding applications. Low maintenance and simple design in a powder paint finish.

Features Include:

- 55" Wheels W/7MM Teeth Standard. 60" Wheels W/7.5MM Teeth Optional
- Ground Clearance With Standard Wheels is and with 60" Wheel Option.
- Rake Teeth are Made of C85 Steel.
- Optional Center Hydraulically Actuated Kicker Wheel
- Dual Wheel Rake Arms, One Side Raking Possible.
- Hydraulic Folding Raking Arms
- Independent Rake Wheel Arms W/Patented Setting Spring System (Allows Adjustment of Ground Pressure without tools.)
- Easy Windrow Width Adjusting System.

Model	HCWR-8	HCWR-10	HCWR-12
# Wheels	8	10	12
Teeth Per Wheel	40	40	40
Wheel Diameter	55"	55"	55"
Max Working Width	18' 5"	21' 8"	24' 3"
Transport Width	9' 2"	9' 2"	9' 2"
Weight LBS	1,387	1,517	1,704

* Unifarm reserves the right to change specifications without notice.

For more information, contact:

Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893

Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997

Email: sales@unifarm.biz Web Site: www.unifarm.biz