

## **FORESTRY MULCHING MOWER** *skid steer attachment*

## **POWER UNLEASHED ...**

Our Forestry Mulching Mower is designed to de-forest an area and return the debris back to the environment. The Rage cuts trees up to 14" in diameter and mulches trees up to 6". If you need a powerful, reliable mulching mower in your arsenal, you need the Forestry Mulcher Mower.

## FEATURES

- Parker Piston Motor is Made in the USA with the highest quality materials and featuring maximum starting torque
- Motor is covered and a storage compartment on deck stores tools such as replacement tooth ratchet
- 1,045 pounds of disc mass unleashes massive amounts of rotational energy to destroy trees and brush
- 1.5" thick disc is the most durable in the industry and consists of one 3/4" plate and two 3/8" plates
- Top deck is made of GR100 steel for maximum strength and durability
- Curved shroud at disc rear creates a smooth, consistent mulching chamber increasing efficiency
- Replaceable carbide bullet teeth are designed to withstand contact with rocks and ground debris
- Perimeter cutting teeth are designed to rotate as they wear and easily replaceable
- Tooth holders are heat treated to withstand tough wear and tear with no cracking
- Tooth protector fins are made 3/4" AR400 steel to protect outer teeth from direct impact
- Front deflector is floating on a pivoted joint to flip up so it's not damaged when encountering obstacles and can also be pinned up during maintenance
- Open front mower easily feeds to the disc and increases visibility
- Exclusively designed slanted push bar positioned forward cuts brush and small trees, horizontally to guide larger trees into mulching chamber, and prevents trees from hanging on deck after cutting
- 4" diameter bearing shaft easily carries the strong forces and weight of disc and has a metal shaft seal protector that turns with the output of the shaft for ultimate protection of the shaft seal

1-546

- Exclusive rasp bars under deck create a fine mulch to minimize plugging and clogging
- Bolting flange uses 12, grade 9 bolts to spread-out stress to help decrease maintenance work

### **FORESTRY MULCHING MOWER** *skid steer attachment*



The covered Parker Piston Motor has a high starting torque and is extremely efficient, high quality, and American made.

800.437.6912

www.erskineattachments.com



Our design incorporates ten top and twelve perimeter cutting teeth with a 4-point design that can be rotated as they wear or if they are damaged. They are convenient and easy to replace with hand tools. Instead of welded to the disc which can cause cracking, those holders are bolted to the disc.



The bottom has 16 durable bullet style carbide tipped teeth that are extremely fast and easy to change. They are designed specifically to go into the ground and can withstand rocky soil conditions without breaking or excessive wear.



Tooth Protector Fins are made of hardened <sup>3</sup>/4" AR400 to protect the outer 8 teeth from direct impact with rocks and other debris.



Floating front deflector faces down to deflect mulch towards the ground.



Unique slanted push bar prevents unwanted trees from hanging on the deck after cutting. This boosts productivity and safety by keeping the operator in the cab and not outside pulling branches off.

# 800.437.6912



#### **ERSKING** www.erskineattachments.com 800.437.6912

## **FORESTRY MULCHING MOWER** *skid steer attachment*



Smartly designed, 17"L x 40"W x 7"H Storage Compartment. Room to store maintenance supplies, tools, and a compartment for the product manual.



Clean deck design reduces amount of debris buildup, is easy to clean off and creates excellent visibility of the front work area.

| Model                     | Mulching Mower            |
|---------------------------|---------------------------|
| Part Number               | 901352                    |
| Motor Type                | Fixed Displacement Piston |
| Cutting Capacity          | Up to 14"                 |
| Mulching Capacity         | Up to 6"                  |
| Operating Weight          | 2,750 lb.                 |
| Height                    | 43"                       |
| Width                     | 70"                       |
| Length                    | 73"                       |
| Cutting Width             | 60"                       |
| Disc Thickness            | 1.5"                      |
| Bearing Carrier           | Oil Bath                  |
| Output Shaft Diameter     | 4"                        |
| Flange Diameter           | 12.38"                    |
| Flange Bolts              | (12) 3/4" Grade 9         |
| Deck Top Material         | 1/2" Grade 100            |
| Disc Mass With Teeth      | 1,045 lb.                 |
| Skid Shoe Material        | 1/2" AR400                |
| Flow Rate                 | 32-45 GPM                 |
| Pressure Range            | 3,000-6,000 PSI           |
| RPM At 40 GPM             | 1,200                     |
| Bottom Carbide Teeth Qty. | 16                        |
| Edge Beaver Teeth Qty.    | 12                        |
| Top Beaver Teeth Qty.     | 10                        |
| Case Drain Line           | Required                  |

# 800.437.6912



Ster

#### **ERSKINE** www.erskineattachments.com 800.437.6912

## **FORESTRY MULCHING MOWER**

SKID STEER ATTACHMENT

