

## **MINI POWER ANGLE BROOM** *MINI SKID STEER ATTACHMENT*



The Mini Power Angle Broom is designed for heavy-duty sweeping of dirt, snow, and other unwanted material. It quickly mounts to your mini skid steer. Featuring a 48" width and optional hydraulic angle change, this attachment is designed to go anywhere to get the job done!

## **FEATURES**

- Direct-Drive design
- Power angling (optional)
- Angles 25° to the right and left
- Storage stands come standard

# 800.437.6912



Ster

#### **ERSKINE** ATTACHMENTS LLC www.erskineattachments.com 800.437.6912

# MINI POWER ANGLE BROOM

MINI SKID STEER ATTACHMENT

Model	Mini Power Angle Broom	
Working Width	48"	
Working Width @ 25° Angle	43.5"	
Overall Width	58.5"	
Maximum Angle (both ways)	25°	
Bristle Diameter	24"	
Rated Flow	7-15 GPM	
Operating psi	2,000 - 3,000 psi	
Weight	280 lb.	
Mounting Kit Configurations	ASV/Terex (RC/PT30)	
	Bobcat (MT-52/55, 463/S70)	
	Toro / Vermeer / Boxer / Ditch Witch / Ramrod / Kanga / Cormidi	
	Universal Mounting Plate (up to 1,000 lb. ROC and within rated flow)	

Options	
Toggle Control Harness*	
Loader Specific Wire Harness*	
Factory Installed Couplers	
Model Description	Part Number
Manual Angling w/poly	900890
Manual Angling w/steel	901300
Manual Angling w/poly/steel	900891
Hydraulic Angling w/poly	900892
Hydraulic Angling w/steel	901301
Hydraulic Angling w/poly/steel	900893
Hydraulic Angling Reversible w/poly	900888
Hydraulic Angling Reversible w/steel	901302
Hydraulic Angling Reversible w/poly/steel	900889
* Applies to hydraulic model only	

# 800.437.6912





### **MINI POWER ANGLE BROOM** *MINI SKID STEER ATTACHMENT*

Easily assembled greaseable bearings for extended wear life

Large 24" Heavy-Duty bristle packages available (sold separately)

Direct-Drive motor gives higher production with lower maintenance \*Standard Manual Model 48" (w/ploy wafer package)



Optional: Wire Harness for hydraulic models with attachment controls. Fits Cat/ASV (8-pin) and John Deere/New Holland/ CASE/Bobcat (14-pin).



Storage stand

Optional: Toggle Control Harness is required if skid steer is NOT equipped with attachment control system. (Only needed when ordering hydraulic angling model)



The direct drive motor turns the broom that angles 25° in both manual and hydraulic configurations.



This unique design allows the broom to better float on the surface and helps to prevent excessive down pressure placed on the broom.

## 800.437.6912

