

TREE SPADE

SKID STEER ATTACHMENT



Turn your skid loader into a high-speed, labor-saving transplanting unit. A tree can be dug or transplanted without the operator having to leave the loader. Spade is designed with a very short frame reducing the need for stabilizers and counterweights. The blades of the tree spade overlap to ensure clean root cutting and support of the root ball.

FEATURES

- Tree Spade comes complete and ready to use, including all-hydraulic hoses, couplers, and controls
- Good for transplanting hardwood trees to 2 1/2" diameter and evergreens to 3"
- Three steel cutting blades are 3/8" thick
- Adjustable control valve stand
- · All joints outfitted with grease fittings
- Removable blades for easy sharpening
- · Short frame design for increased down-pressure reducing the need for rear stabilizers

800.437.6912



ERSKINE ATTACHMENTS LLC

www.erskineattachments.com 800.437.6912

TREE SPADE

SKID STEER ATTACHMENT



This Tree Spade has full hydraulic controls for in-cab operation and is fully adjustable to fit most skid steers.



Overlapping blades ensure a clean cut and support o root ball.	f the

Model	3S	4S
Part Number	901165	901166
Tree Size (Evergreen)	3"	4"
Tree Size (Hardwood)	2.5"	3"
Root Ball Diameter	30"	40"
Root Ball Depth	29"	30"
Blade Angle	25°	25°
Number of Blades	3	4
Blade Thickness	3/8" A36 Steel	1/4" Grade 50 Steel
Slides	Steel	Steel
Blade Truncation	Semi	Full
Outside Towers Swing Open	Yes	Yes
Operator Controls	Hydraulic	Hydraulic
Hydraulic Flow	5-25 GPM @ 2,500 psi	5-25 GPM @ 2,500 psi
Hydraulic Remotes	1	1
Shipping Weight	1,500 lb.	1,900 lb.
Weight with Root Ball	2,000 lb.	3,100 lb.
Width (Bottom / Top)	46" / 84"	62" / 78"
Length (Bottom / Top)	52" / 76"	61" / 76"

Options External Control (wired) External Control (wireless) Factory Installed Couplers

800.437.6912

ERSKINE ATTACHMENTS LLC



TREE SPADE

SKID STEER ATTACHMENT





Short frame design reduces the need for stabilizers and counterweights.



Turn your skid loader into a high-speed, labor-saving transplanting unit.

800.437.6912

