



# **BELT RAKE**

### FEATURES:

- Forms a light and airy windrow (not braided)
- Turns any type of hay, even at high speed
- Cat. 1, 3-point hitch
- Requires minimum 20HP tractor to operate

MODELS	DESCRIPTION	WEIGHT
GSE-220	Belt Rake, 87" Working Width	694

## FINGERWHEEL RAKES

### **FEATURES**:

- For turning, windrowing, spreading and raking
- Sturdy construction
- Cat. 1, 3-point hitch
- 55" diameter wheels, 40 teeth per wheel
- Wheels mounted on roller bearings



MODELS	DESCRIPTION	WEIGHT
RP-2	2 Wheel, 3-point Windrow Turner	145
RP-3	3 Wheel, 3-point Windrow Turner	210
RP-4	4 Wheel, 3-point Side Delivery Rake	366



# **QUICK RAKES**

#### **FEATURES**:

- Rake folds to transport when lifted
- Choice of 8, 10, or 12 wheels
- Adjustable wheel pressure
- Follows uneven terrain
- Includes hydraulic cylinders and hoses

MODELS	DESCRIPTION	WEIGHT
QR-8	8 Wheel Quick Rake, 18' working width	1500
QR-10	10 Wheel Quick Rake, 21' working width	1630
QR-12	12 Wheel Quick Rake, 24'-6" working width	1830
230-371	Center Wheel Kit, QR Series	
230-735	Hydraulic Angle Kit, QR-8 and QR-10	
230-736	Hydraulic Angle Kit, QR-12	