

ROTARY CUTTER



Heavy Duty Skid



Heavy Duty Welded Deck



Standard Chain Guard



Standard Slip Clutch

SPECIFICATIONS

CATEGORY	4' MRC3048-SC	5' MRC3060-SC	6' MRC5072-SC	7' MRC5084-SC
Gear Box	40hp Heavy Duty	50hp Heavy Duty	75hp Heavy Duty	83hp Heavy Duty
Gear Box Mount			3/8" Steel	
Deck Thickness		10 Gauge Solid Welded		10 Gauge With 7 Gauge Center Solid Welded
Skirt Thickness			10 Gauge Steel	
Skid Shoes			1/4" Replaceable	
Lift Attachment Brackets			1/2" Solid Welded	
Tail-Wheel Arm		2-1/2" X 2-1/2" X .180" Designed To Withstand Rear Tractor Wheel Lift Off		
Tail-Wheel		4" X 15" Puncture Resistant Bushing Style		
Stump Jumper	12 Splined, Standard Duty, Pan Style	15 Splined, Standard Duty, Pan Style	15 Splined, Heavy Duty, Reinforced Round Stump Jumper	15 Splined, Standard Duty, Pan Style
Warranty			1 Year Limited	
Weight	600 lbs.	718 lbs.	880 lbs.	1,100 lbs.
Length (Including Tail-Wheel)	88"	104"	116"	120 1/2"
Total Width	53 1/2"	65 1/2"	78"	53 1/2"
Overall Height	36 1/2"		37"	92 1/2"
Deck Height		7"	8 3/4"	9"
Cut Range		2" – 10"	3"	3" – 6 1/4"
PTO Drive Shaft	Series 4 Shear Bolt Or Series 4 Slip Clutch		Series 6 Shear Bolt Or Series 6 Slip Clutch	
Blades		1/2" X 3"		31" X 1/2" X 4" (28 1/2" Working Length)
Tractor Range	24 – 40hp		35 – 72hp	35 – 83hp
Cutting Capacity			2" Diameter	
Blade Tip Speed	13,093 ft/min	16,366 ft/min	14,856 ft/min	13,605 ft/min
3-Point Hitch		Category 1		Category 2
Blade Spindle			1	
Tractor PTO rpm			540	