PHOENIX

T30 Series Rotary Tillers Heavy Duty Tillers from 90 to 120 Inches (90-160 HP)





T30 Series Gear Drive Rotary Tillers from Phoenix are extremely reliable and suited to even the most demanding applications and soil conditions. The super strong frame, heavy duty steel plate box-type bonnet, and four speed side drive in oil bath make these heavy duty machines dependable work horses on any job. From the oversized rotor tube with optional double flange to the double extended torque tubes, this machine is built to give you years of trouble free service.

Get the most out of your T30 Series Rotary Tiller with optional Roller Packer Kit, Hydraulic Roller Packer Control Kit, and Double Flanged Rotor Tube.

Standard Features Include:

- Series 8 PTO Clutch With 4 Plate Slip Clutch by Eurocardan
- 6 Heavy Duty Tines Per Flange
- 2+2 Gearbox
- Gear Drive Transmission in Oil Bath
- Double Torque Tube

Available Options on Request:

- Double Flanges
- Roller Packer Kit
- Hydraulic Roller Packer Control Kit
- Spiked Roller Packer Kit

SPECIFICATIONS	T30-90GE	T30-100GE	T30-112GE	T30-120GE
Working Width (in.)	90	100	112	120
Working Depth (in.)	4-8	4-8	4-8	4-8
Blades/Flange	6	6	6	6
Total Blades	54	60	66	72
Transmission	Gear Drive	Gear Drive	Gear Drive	Gear Drive
Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch
PTO Shaft Series	8	8	8	8
PTO Requirement (HP)	90-160	90-160	90-160	90-160
Rotor Flange Diameter (in.)	6.3	6.3	6.3	6.3
Rotor Flange Thickness (in.)	0.6	0.6	0.6	0.6
Approximate Weight W/PTO (LBS)	2515	2725	2879	3108
Rotor Speeds	2+2	2+2	2+2	2+2

* Unifarm reserves the right to change specifications without notice.

For more information contact: Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road,Wilson, NC 27893 Phone:252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997 Email: sales@unifarm.biz Website: www.unifarmmachinery.com