



# V-RIPPERS



**STANDARD & HEAVY-DUTY SERIES V-RIPPERS:** Standard Duty Series are recommended for breaking up hardpan and compacted soil for improved soil aeration and increased yields. The 4" x 6" x 84" width tool bar is equipped with category 2, 3-point hitch, for tractors 50-80 HP and available with either 2 or 3 shanks. The 1" x 27" parabolic shanks are shear-bolt protected and equipped with high carbon heat-treated points. Standard series is quick hitch compatible. Heavy-Duty Series are ideal for deep ripping and break up of compacted soil to increase root growth, water penetration and yield. The rugged 5" x 7" tool bar is equipped with category 2 and 3, 3-point hitch, for tractors 80-195 HP, 3-shank model is available with 84" tool bar, 5 and 7 shank models with 144" tool bar widths. The high clearance 1-1/4" x 34" parabolic shanks are shear-bolt protected and equipped with high carbon heat-treated points.

MODELS	NO. OF SHANKS	TOOL BAR WIDTH	FRAME TUBE SIZE	SHANK	SHANK SIZE	HITCH	MAX. HP	WEIGHT
VR-227	2	84"	4" x 6"	27"	1" Parabolic	Cat. 2	80	675
VR-327	3	84"	4" x 6"	27"	1" Parabolic	Cat. 2	80	750
VR-327-HF	3	84"	4" x 6"	27"	1" Parabolic	Cat. 2	80	759
VR-334	3	84"	5" x 7"	34"	1-1/4" Parabolic	Cat. 2 & 3	85	850
VR-334-HF	3	84"	5" x 7"	34"	1-1/4" Parabolic	Cat. 2 & 3	85	865
VR-534	5	144"	5" x 7"	34"	1-1/4" Parabolic	Cat. 2 & 3	140	1700
VR-534-HF	5	144"	5" x 7"	34"	1-1/4" Parabolic	Cat. 2 & 3	140	1725
VR-734	7	144"	5" x 7"	34"	1-1/4" Parabolic	Cat. 2 & 3	195	2080
VR-734-HF	7	144"	5" x 7"	34"	1-1/4" Parabolic	Cat. 2 & 3	195	2110

***Innovative, Rugged & Labor Saving Attachments***