



**QUICK HITCH  
COMPATIBLE**

## REGULAR DUTY CUTTERS

### FEATURES:

- Flexible floating 3-pt. hitch
- Laminated tailwheel
- 10 gauge deck and side bands with angle iron cross bracing
- Side bands have full length skids
- SAE Cat.3 driveline with shear bolt protection
- 40 HP gearbox
- Round blade holder w/ uplift blades
- Available in tractor matching colors

Optional Equipment: Belt Guards and Chain Guards

MODELS	CUTTING WIDTH	HITCH	CUTTING HEIGHT	CUTTING CAPACITY	BLADE SIZE	DECK THICKNESS	GEARBOX RATING	DRIVELINE SAFETY	WEIGHT
TC07-340	40"	Cat. 1	1" to 8"	1"	1/2" X 3"	10 Gauge	40 HP	Shear Bolt	400
TC10-400	48"	Cat. 1	1" to 8"	1"	1/2" X 3"	10 Gauge	40 HP	Shear Bolt	425
TC10-500	60"	Cat. 1	1" to 8"	1"	1/2" X 3"	10 Gauge	40 HP	Shear Bolt	525
TC10-600	72"	Cat. 1	1" to 8"	1"	1/2" X 3"	10 Gauge	40 HP	Shear Bolt	625

## MEDIUM DUTY CUTTERS

### FEATURES:

- Flexible floating 3-pt. hitch
- Laminated tailwheels
- 11 gauge deck with 3/16" side bands
- Side bands have full length skids
- SAE Cat. 5 driveline with slip clutch
- 75 HP gearbox
- Round blade holder w/ uplift blades
- Available in tractor matching colors

Optional Equipment: Chain Guards



MODELS	CUTTING WIDTH	HITCH	CUTTING HEIGHT	CUTTING CAPACITY	BLADE SIZE	DECK THICKNESS	GEARBOX RATING	DRIVELINE SAFETY	WEIGHT
TC94-700-MC	84"	Cat. 1	1" - 8"	1-1/2"	1/2" X 3-1/2"	11 gauge	75 HP	Slip Clutch	1000



**WARNING:** For non-agricultural use, OSHA, ASAE, SAE and ANSI standards require the use of chain guards or other protective guards at all times. We also strongly recommend the use of such guards for agricultural uses to reduce the risk of property damage, serious bodily injury or even death from objects thrown out by or from contact with the cutting blades.



## MEDIUM DUTY CUTTERS

### FEATURES:

- Flexible floating 3-pt. hitch
- Laminated tailwheels
- 1/4" side bands
- Side bands have full length skids
- SAE Cat. 5 driveline with slip clutch
- Round blade holder w/ uplift blades
- Available in tractor matching colors

Optional Equipment: Chain Guards

MODELS	CUTTING WIDTH	HITCH	CUTTING HEIGHT	CUTTING CAPACITY	BLADE SIZE	DECK THICKNESS	GEARBOX RATING	DRIVELINE SAFETY	WEIGHT
TC96-700-MC	84"	Cat. 1	1" - 8"	1-1/2"	1/2" X 3-1/2"	11 gauge	90 HP	Slip Clutch	1000
TC96-800-MC	96"	Cat. 2	2" - 12"	2"	1/2" X 3-1/2"	10 gauge	90 HP	Slip Clutch	1420
TC96-1000-MC	120"	Cat. 2	2" - 12"	2"	1/2" X 3-1/2"	10 gauge	90 HP	Slip Clutch	1520

## VARIABLE OFFSET CUTTERS

### FEATURES:

- Heavy duty construction 10 gauge deck & 1/4" side band
- Low profile laminated tailwheels
- Variable offset, Cat. 2, semi-mount hitch is hydraulically controlled and provides up to 60" offset right of center
- Heavy duty series 5 driveline equipped with a slip clutch for protection
- Equipped with heavy duty uplift blades and round blade holders
- 120 HP center gearbox - 90 HP outer gearboxes

Optional Equipment: Chain Guards



MODELS	CUTTING WIDTH	HITCH	CUTTING HEIGHT	CUTTING CAPACITY	BLADE SIZE	DECK THICKNESS	GEARBOX RATING	PTO SHAFT	WEIGHT
TC94-700	84"	Cat. 2	2" - 12"	2"	1/2" X 3-1/2"	10 gauge	90 HP	Slip Clutch	1640
TC94-800	96"	Cat. 2	2" - 12"	2"	1/2" X 3-1/2"	10 gauge	90 HP	Slip Clutch	1740



**WARNING:** For non-agricultural use, OSHA, ASAE, SAE and ANSI standards require the use of chain guards or other protective guards at all times. We also strongly recommend the use of such guards for agricultural uses to reduce the risk of property damage, serious bodily injury or even death from objects thrown out by or from contact with the cutting blades.