

3-POINT SPRAYERS

LG SERIES

FEATURES:

- 25, 40, 55, 110, 150 & 200 gallon corrosion resistant polyethylene tanks
- Lever valve boom controls
- Relief valve with pressure gauge
- Standard or Silvercast pumps
- 3-way boom control on 110, 150 & 200 gallon



MODELS	HITCH	GALLONS	GPM	PSI	PUMP	WEIGHT
LG-27-3PT	Cat. 1	25	9.76	300	Cast	103
7V00048	Cat. 1	40	2.2	60	12 Volt	80
LG55-3PT	Cat. 1	55	9.76	300	Cast	180
LG-110-3PT	Cat. 1 or 2	110	9.76	300	Cast	388
LG-150-3PT	Cat. 1 or 2	150	9.76	300	Cast	449
LG-200-3PT	Cat. 1 & 2	200	9.76	300	Cast	511

Note: Optional roundup resistant silvercast pumps available - add XL to the model number.

SPRAY BOOMS

MODELS	SPRAY WIDTH	BOOM TYPE	NOZZLE TYPE	# OF NOZZLES	NOZZLE SPACING	WEIGHT
BK-70A	140"	Folding	Fan	7	20"	21
257-6	21'	Folding	Fan	13	20"	82
257-8	28'	Folding	Fan	17	20"	96
257-10	35'	Folding	Fan	21	20"	110

RANKIN

SPRAYERS

SPOT ● ATV ● UTILITY ● SKID
TRAILER ● 3-POINT



Innovative, Rugged & Labor Saving Attachments



RANKIN
EQUIPMENT CO

Phone (800) 426-2009 (509) 453-8271

www.rankinequipment.com

www.rankinequipment.com

SPOT SPRAYERS

LG SERIES

FEATURES:

- 15, 25 & 40 gal. corrosion resistant polyethylene tanks
- 12 volt diaphragm high-flo pump
- Detachable power harness with battery clips
- Moldboard wand clips

Pump and motor stop instantly when discharge is closed. Diaphragm design eliminates troublesome shaft seal. Pump can be run indefinitely without damage. Ball bearing drive assures longer pump life. Excellent self-priming capability. Santoprene diaphragms and vitron valves are standard. Maximum temperature of pumped liquid 160°F (71°C). Permanent magnet motor and longer life brushes.



High-Flo Pump



LG-15-EC

LG-40-SS



LG-28-S

MODELS	GALLONS	GPM	PSI	HAND GUN	HOSE	WEIGHT
LG-15-EC	15	1.0	35	Lever	15'	30
LG-13-P	15	2.4	60	Lever	15'	30
LG-28-S	25	2.4	60	Pistol Grip	15'	30
LG-40-SS	40	4.5	60	Pistol Grip	25'	90

ATV SPRAYERS

ATV BOOM SERIES

FEATURES:

- 25 gallon corrosion resistant polyethylene tanks
- 12 volt diaphragm high-flo pump
- Detachable power harness with battery clips
- Moldboard wand clips
- Pressure Gauge

ATV sprayers include the premium high-flo pump with a demand switch that operates only when liquid flow is required. Pump and motor stop instantly when discharge is closed. Diaphragm design eliminates troublesome shaft seal. Pump can be run indefinitely without damage. Ball bearing drive assures longer pump life. Excellent self-priming capability. Santoprene diaphragms and vitron valves are standard. Maximum temperature of pumped liquid 160°F (71°C). Permanent magnet motor and longer life brushes.



High-Flo Pump



LG-3025



ATV-25-71

MODELS	GALLONS	GPM	PSI	HAND GUN	HOSE	BOOM NOZZLES	COVERAGE	WEIGHT
ATV-25-71	25	4.5	60	Lever	15'	7	140"	70
LG-3025	25	4.5	60	Pistol Grip	15'	3	30'	50

TRAILER SPRAYERS

TRAILER BOOM SERIES

FEATURES:

- 15, 25 & 40 gallon corrosion resistant polyethylene tanks
- 12 volt diaphragm high-flo pump
- Detachable power harness with battery clip
- Molded wand clips
- Pneumatic tires
- Pressure gauge

All trailer sprayers include the premium high-flo pump with a demand switch that operates only when liquid flow is required. Pump and motor stop instantly when discharge is closed. Diaphragm design eliminates troublesome shaft seal. Pump can be run indefinitely without damage. Ball bearing drive assures longer pump life. Excellent self-priming capability. Santoprene diaphragms and vitron valves are standard. Maximum temperature of pumped liquid 160°F (71°C). Permanent magnet motor and longer life brushes.



High-Flo Pump



LG-2500-303



TR-40-EX

MODELS	GALLONS	GPM	PSI	HAND GUN	HOSE	BOOM NOZZLES	COVERAGE	WEIGHT
LG-2500-303	25	2.4	60	Lever	15'	2	80"	70
TR-40-EX	40	2.4	60	Pistol Grip	25'	5	100"	205

UTILITY / SKID SPRAYERS

UTL / SK SERIES

FEATURES:

- 45 and 65 gallon corrosion resistant polyethylene tanks
- 12 volt high-flo or 4 roller pump (SK Series)
- Detachable power harness with battery clips
- Pressure gauge
- Ideal for utility vehicles

All UTL sprayers include the premium high-flo pump with a demand switch that operates only when liquid flow is required. Pump and motor stop instantly when discharge is closed. Diaphragm design eliminates troublesome shaft seal. Pump can be run indefinitely without damage. Ball bearing drive assures longer pump life. Excellent self-priming capability. Santoprene diaphragms and vitron valves are standard. Maximum temperature of pumped liquid 160°F (71°C). Permanent magnet motor and longer life brushes.



High-Flo Pump



UTV-65-7



UTV-65-BL



SK-61-4R

MODELS	GALLONS	GPM	PSI	HAND GUN	HOSE	BOOMNOZZLES	COVERAGE	WEIGHT
UTV-65-7	65	4.5	60	Pistol Grip	25'	7	140"	173
UTV-65-BL	65	4.5	60	Pistol Grip	25'	3	30'	166
SK-61-4R	60	6.0	120	Pistol Grip	25'	Optional		205