

# RANKIN

## SPRAYERS

SPOT ● ATV ● UTILITY ● SKID  
TRAILER ● 3-POINT



*Innovative, Rugged & Labor Saving Attachments*



# SPOT SPRAYERS

## LG SERIES



LG-15-EC

LG-28-SS

LG-40-SS

### FEATURES:

- 15, 25 & 40 gal. corrosion resistant polyethylene tanks
- 12 volt diaphragm high-flo pump
- Detachable power harness with battery clips
- Moldboard wand clips

Pump and motor stop instantly when discharge is closed. Diaphragm design eliminates troublesome shaft seal. Pump can be run indefinitely without damage. Ball bearing drive assures longer pump life. Excellent self-priming capability. Santoprene diaphragms and vitron valves are standard. Maximum temperature of pumped liquid 160°F (71°C). Permanent magnet motor and longer life brushes.



MODELS	GALLONS	GPM	PSI	HAND GUN	HOSE	WEIGHT
LG-15-EC	15	1.0	35	Lever	15'	30
LG-13-P	15	2.1	60	Lever	15'	30
LG-28-SS	25	2.1	60	Pistol Grip	15'	30
LG-40-SS	40	3.8	45	Pistol Grip	25'	90

# ATV SPRAYERS

## ATV BOOM SERIES



LG-3025

ATV-15-2

### FEATURES:

- 15, 25 gallon corrosion resistant polyethylene tanks
- 12 volt diaphragm high-flo pump
- Detachable power harness with battery clips
- Moldboard wand clips
- Pressure Gauge

ATV sprayers include the premium high-flo pump with a demand switch that operates only when liquid flow is required. Pump and motor stop instantly when discharge is closed. Diaphragm design eliminates troublesome shaft seal. Pump can be run indefinitely without damage. Ball bearing drive assures longer pump life. Excellent self-priming capability. Santoprene diaphragms and vitron valves are standard. Maximum temperature of pumped liquid 160°F (71°C). Permanent magnet motor and longer life brushes.



MODELS	GALLONS	GPM	PSI	HAND GUN	HOSE	BOOM NOZZLES	COVERAGE	WEIGHT
ATV-15-2	15	2.1	60	Lever	15'	2	80"	36
ATV-25-71	25	3.8	45	Lever	15'	7	140"	70
LG-3025	25	3.8	45	Pistol Grip	15'	3	30'	50

# TRAILER SPRAYERS

## FEATURES:

- 15, 25 & 40 gallon corrosion resistant polyethylene tanks
- 12 volt diaphragm high-flo pump
- Detachable power harness with battery clip
- Molded wand clips
- Pneumatic tires
- Pressure gauge

All trailer sprayers include the premium high-flo pump with a demand switch that operates only when liquid flow is required. Pump and motor stop instantly when discharge is closed. Diaphragm design eliminates troublesome shaft seal. Pump can be run indefinitely without damage. Ball bearing drive assures longer pump life. Excellent self-priming capability. Santoprene diaphragms and vitron valves are standard. Maximum temperature of pumped liquid 160°F (71°C). Permanent magnet motor and longer life brushes.



High-Flo Pump

## TRAILER BOOM SERIES



LG-2500-303

TR-40-EX

MODELS	GALLONS	GPM	PSI	HAND GUN	HOSE	BOOM NOZZLES	COVERAGE	WEIGHT
LG-1500-303	15	2.1	60	Lever	15'	2	80"	65
LG-2500-303	25	2.1	60	Lever	15'	2	80"	70
TR-40-EX	40	2.1	60	Pistol Grip	25'	5	100"	205

# UTILITY / SKID SPRAYERS

## FEATURES:

- 40 and 60 gallon corrosion resistant polyethylene tanks
- 12 volt high-flo or 4 roller pump
- Detachable power harness with battery clips
- Pressure gauge
- Ideal for utility vehicles

All UTL sprayers include the premium high-flo pump with a demand switch that operates only when liquid flow is required. Pump and motor stop instantly when discharge is closed. Diaphragm design eliminates troublesome shaft seal. Pump can be run indefinitely without damage. Ball bearing drive assures longer pump life. Excellent self-priming capability. Santoprene diaphragms and vitron valves are standard. Maximum temperature of pumped liquid 160°F (71°C). Permanent magnet motor and longer life brushes.



High-Flo Pump

## UTL / SK SERIES



UTL-40-5

UTL-40-12VBL

SK-61-4R

MODELS	GALLONS	GPM	PSI	HAND GUN	HOSE	BOOM NOZZLES	COVERAGE	WEIGHT
UTL-40-5	40	2.1	60	Pistol Grip	25'	5	100"	167
UTL-40-12VBL	40	3.8	45	Pistol Grip	25'	3	30'	128
UTL-60-12V	60	3.8	45	Pistol Grip	25'	5	100"	173
UTL-60-12VBL	60	3.8	45	Pistol Grip	25'	3	30'	166
SK-61-4R	60	6.0	120	Pistol Grip	25'	Optional	100" - 140"	205

# 3-POINT SPRAYERS

**LG-40-3PT-12V**

**LG-110-3PT**



## FEATURES:

- 25, 40, 55, 110, 150, & 200 gallon high quality polyethylene tanks
- Cat. 1, 3-point hitch
- Heavy formed steel frames
- Pressure gauge and relief valve
- Large main strainer
- Standard or XL Silvercast pumps
- Quick coupler adapter to PTO connection
- 3-way boom control valve on 110, 150, & 200 gallon
- Opt. 21', 28' & 35' spray booms, 120" standard on 40 gallon - 140" on 25 & 55 gallon
- Breakaway hinges on booms
- Molded in sight gauge markings
- 5" fill opening
- Optional hand gun and hose kit

MODELS	HITCH	GALLONS	GPM	PSI	PUMP	WEIGHT
LG-27-3PT	Cat. 1	25	9.76	300	Cast	103
LG-40-3PT-12V	Cat. 1	40	2.1	60	12-Volt	80
LG55-3PT	Cat. 1	55	9.76	300	Cast	180
LG-110-3PT	Cat. 1 or 2	110	9.76	300	Cast	388
LG-150-3PT	Cat. 1 or 2	150	9.76	300	Cast	449
LG-200-3PT	Cat. 1 & 2	200	9.76	300	Cast	511

Note: Optional roundup resistant silvercast pumps available - add XL to the model number.

## SPRAY BOOMS

MODELS	SPRAY WIDTH	BOOM TYPE	NOZZLE TYPE	# OF NOZZLES	NOZZLE SPACING	WEIGHT
BK-70A	140"	Folding	Fan	7	20"	21
257-6	21'	Folding	Fan	13	20"	82
257-8	28'	Folding	Fan	17	20"	96
257-10	35'	Folding	Fan	21	20"	110



Phone (800) 426-2009 / (509) 453-8271 • Fax: (509) 457-2456

**EQUIPMENT CO**

[www.rankineqco.com](http://www.rankineqco.com)

Revised January 2015