

## SPOT SPRAYERS



### LG SERIES

#### FEATURES:

- 25 gallon corrosion resistant polyethylene tanks
- 12 volt diaphragm high-flo pump
- Detachable power harness with battery clips
- Moldboard wand clips

Pump and motor stop instantly when discharge is closed. Diaphragm design eliminates troublesome shaft seal. Pump can be run indefinitely without damage. Ball bearing drive assures longer pump life. Excellent self-priming capability. Santoprene diaphragms and vitron valves are standard. Maximum temperature of pumped liquid 160°F (71°C). Permanent magnet motor and longer life brushes.



High-Flo Pump

MODELS	GALLONS	GPM	PSI	HAND GUN	HOSE	WEIGHT
LG-28-S	25	2.4	60	Pistol Grip	15'	30

## ATV SPRAYERS



LG-3025-QR



ATV-25-71

#### FEATURES:

- 25 gallon corrosion resistant polyethylene tanks
- 12 volt diaphragm high-flo pump
- Detachable power harness with battery clips
- Moldboard wand clips
- Pressure Gauge

ATV sprayers include the premium high-flo pump with a demand switch that operates only when liquid flow is required. Pump and motor stop instantly when discharge is closed. Diaphragm design eliminates troublesome shaft seal. Pump can be run indefinitely without damage. Ball bearing drive assures longer pump life. Excellent self-priming capability. Santoprene diaphragms and vitron valves are standard. Maximum temperature of pumped liquid 160°F (71°C). Permanent magnet motor and longer life brushes.



High-Flo Pump

MODELS	GALLONS	GPM	PSI	HAND GUN	HOSE	BOOM NOZZLES	COVERAGE	WEIGHT
ATV-25-71	25	4.5	60	Lever	15'	7	140"	70
LG-3025-QR	25	4.5	60	Pistol Grip	15'	3	30'	50

**Innovative, Rugged & Labor Saving Attachments**

www.rankinequipment.com

February 2024

# RANKIN

## SPRAYERS



### 3-Point • Trailer • Spot • ATV



**Innovative, Rugged & Labor Saving Attachments**

www.rankinequipment.com

## 3-POINT SPRAYERS



LG-45



LG-65

### LG SERIES

**FEATURES:**

- 45, 65, 110, & 200 gallon corrosion resistant polyethylene tanks
- Lever valve boom controls
- Relief valve with pressure gauge
- Standard or Silvercast pumps
- 3-way boom control on 110, 150 & 200 gallon

MODELS	HITCH	GALLONS	GPM	PSI	PUMP	WEIGHT
LG-45-3PT-12V	Cat. 1	45	2.2	60	12 Volt	80
LG-65-3PT	Cat. 1	65	9.76	300	Cast	180
LG-110-3PT	Cat. 1 or 2	110	9.76	300	Cast	388
LG-200-3PT	Cat. 1 & 2	200	9.76	300	Cast	511

Note: Optional roundup resistant silvercast pumps available - add XL to the model number.

### SPRAY BOOMS

MODELS	SPRAY WIDTH	BOOM TYPE	NOZZLE TYPE	# OF NOZZLES	NOZZLE SPACING	WEIGHT
BK-70A	140"	Folding	Fan	7	20"	21
257-6	21'	Folding	Fan	13	20"	82
257-8	28'	Folding	Fan	17	20"	96
257-10	35'	Folding	Fan	21	20"	110

Specifications subject to change without notice

## TRAILER SPRAYERS



LG-30-TRL



TR-45-EX

### TRAILER BOOM SERIES

**FEATURES:**

- 30 & 40 gallon corrosion resistant polyethylene tanks
- 12 volt diaphragm high-flo pump
- Detachable power harness with battery clip
- Molded wand clips
- Pneumatic tires
- Pressure gauge

All trailer sprayers include the premium high-flo pump with a demand switch that operates only when liquid flow is required. Pump and motor stop instantly when discharge is closed. Diaphragm design eliminates troublesome shaft seal. Pump can be run indefinitely without damage. Ball bearing drive assures longer pump life. Excellent self-priming capability. Santoprene diaphragms and vitron valves are standard. Maximum temperature of pumped liquid 160°F (71°C). Permanent magnet motor and longer life brushes.



High-Flo Pump



MODELS	GALLONS	GPM	PSI	HAND GUN	HOSE	BOOM NOZZLES	COVERAGE	WEIGHT
LG-30-TRL	30	2.4	60	Lever	15'	2	80"	70
TR-45-EX	45	2.4	60	Pistol Grip	25'	5	100"	205

Specifications subject to change without notice