



## Snow Pushers 24-Series

Engineered to fit compact tractors equipped with a loader. The 24-Series Snow Pusher is job matched to the tractor for maximum performance.

- Replaceable 1" x 6" reversible Ultra-Rubber cutting edge is standard on "R" models
- Replaceable 3/8" x 6" reversible steel cutting edge is standard on "M" models
- Models to fit loaders with "Universal" skid steer attaching system.
- Models to fit John Deere 200/300/400 series loaders with quick attach system.
- All models feature adjustable & reversible skid shoes of AR-400 steel.



### 24-Series Snow Pusher Specifications For Tractors up to 50 HP, Max., "Universal" Skid Steer Attach

	SPS-2460R	SPS-2460M	SPS-2472R	SPS-2472M	SPS-2484R	SPS-2484M
Overall Width (in/cm)	66.5 / 169	66.5 / 169	78.5 / 199.4	78.5 / 199.4	90.5 / 230	90.5 / 230
Overall Height (in/cm)	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65
Overall Depth (in/cm)	26 / 66	26 / 66	26 / 66	26 / 66	26 / 66	26 / 66
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
End Plate Thickness (in/cm)	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635
Reinforced Endplates	Yes	Yes	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes	No	Yes	No	Yes	No
Steel Cutting Edge	No	Yes	No	Yes	No	Yes
Skid Shoes of AR-400	Std.	Std.	Std.	Std.	Std.	Std.
Horsepower Rating	20-30 HP	20-30 HP	25-40 HP	25-40 HP	30-50 HP	30-50 HP
Operating Weight of Power Unit	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.
Weight (lbs/kg)	390 / 177	410 / 186	430 / 195	450 / 204	465 / 211	485 / 220
Product No.	358000	358005	358010	358015	358020	358025
Optional Pull-Back Kit	358095	358095	358105	358105	358115	358115
Optional Poly Skid Shoes	358245	358245	358245	358245	358245	358245

### 24-Series Snow Pusher Specifications For John Deere Tractors up to 50 HP, Max.

John Deere Hook & Pin Quick Attach for 200/300/400, D120, D160, D170, H120, H130, H160, H165, H180

	SPJD-2460R	SPJD-2460M	SPJD-2472R	SPJD-2472M	SPJD-2484R	SPJD-2484M
Overall Width (in/cm)	66.5 / 169	66.5 / 169	78.5 / 199.4	78.5 / 199.4	90.5 / 230	90.5 / 230
Overall Height (in/cm)	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65	25.6 / 65
Overall Depth (in/cm)	26 / 66	26 / 66	26 / 66	26 / 66	26 / 66	26 / 66
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
End Plate Thickness (in/cm)	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635	1/4 / 0.635
Reinforced Endplates	Yes	Yes	Yes	Yes	Yes	Yes
Rubber Cutting Edge	Yes	No	Yes	No	Yes	No
Steel Cutting Edge	No	Yes	No	Yes	No	Yes
Skid Shoes of AR-400	Std.	Std.	Std.	Std.	Std.	Std.
Horsepower Rating	20-30 HP	20-30 HP	25-40 HP	25-40 HP	30-50 HP	30-50 HP
Operating Weight of Power Unit	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.	3,500 lbs. Max.
Weight (lbs/kg)	379 / 172	399 / 181	415 / 188	435 / 197	450 / 204	470 / 213
Product No.	358030	358035	358040	358045	358050	358055
Optional Pull-Back Kit	358095	358095	358105	358105	358115	358115
Optional Poly Skid Shoes	358245	358245	358245	358245	358245	358245



**WARNING:** Read and understand the operator's manual before operation. Be sure tractor/skid steer are properly counterbalanced. Damage to equipment or personal injury could occur.